

# REFRACTORY BLADES

**REFRACTORY BLADES ARE AVAILABLE IN A MULTITUDE OF SPECIFICATIONS IN ORDER TO REACH THE FASTEST CUTTING AND HIGHEST PERFORMANCE RESULTS FOR WHATEVER TYPE OF BRICK IS BEING CUT.**

Diamond refractory blades are used primarily in the refurbishment and restoration of refractory furnaces. Refractory blades offered by Penhall are manufactured to meet the unique high demands of this extremely hard material. 14", 18", and 20" wet cutting blades are offered in four specifications to meet the widest application range.



## Refractory Blade Recommended Specifications

APPLICATION	14 X 1	18 X 1	20 X 1
GENERAL PURPOSE	NXWRGP1401	NXWRGP1801	NXWRGP2001
HARD	NXWRHD1401	NXWRHD1801	NXWRHD2001
MEDIUM	NXWRMD1401	NXWRMD1801	NXWRMD2001
SOFT	NXWRSF1401	NXWRSF1801	NXWRSF2001

# DIAMOND REFRACTORY BLADES

## Refractory Blade (Wet Cutting) List Prices

UPC	ITEM #	SIZE	BORE	SEMENT HEIGHT	LIST PRICE
<b>GENERAL PURPOSE REFRACTORY – WET</b>					
701846 81458 4	NXWRGP1401	14 X .100	1"	0.282	\$950
701846 81459 1	NXWRGP1801	18 X .125	1"	0.282	1,350
701846 81460 7	NXWRGP2001	20 X .125	1"	0.282	1,505
<b>HARD REFRACTORY – WET</b>					
701846 81348 8	NXWRHD1401	14 X .100	1"	0.326	\$950
701846 81456 0	NXWRHD1801	18 X .125	1"	0.326	1,350
701846 81457 7	NXWRHD2001	20 X .125	1"	0.326	1,505